



CLASSIFICATION		DIMENSION	
EXTERNAL	LENGTH	6058 ⁰ ₋₆	19' - 10 1/2" ⁰ _{-1/4"}
	WIDTH	2438 ⁰ ₋₅	8' - 0" ⁰ _{-3/16"}
	HEIGHT	2591 ⁰ ₋₅	8' - 6" ⁰ _{-3/16"}
INTERNAL	LENGTH	5898 ⁰ ₋₆	19' - 4 13/64" ⁰ _{-1/4"}
	WIDTH	2352 ⁰ ₋₅	7' - 8 19/32" ⁰ _{-3/16"}
	HEIGHT	2393 ⁰ ₋₅	7' - 10 7/32" ⁰ _{-3/16"}
DOOR OPENING	WIDTH	2340 ⁰ ₋₅	7' - 8 1/8" ⁰ _{-3/16"}
	HEIGHT	2280 ⁰ ₋₅	7' - 5 49/64" ⁰ _{-3/16"}
INTERNAL CUBIC CAPACITY		33.2 M ³	1170 FT ³

MAX GROSS WEIGHT	30480 KGS	67200 LBS
TARE WEIGHT	2100 KGS	4630 LBS
MAX PAY LOAD	28380 KGS	62570 LBS
STACKING TEST LOAD	97200 KGS	214290 LBS
FLOOR STRENGTH	7260 KGS	16000 LBS

6	MARKING ARRANGEMENT	18NE22M	24A-00	1
5	ROOF ASSEMBLY	18NE22R	24A-00	1
4	BASE ASSEMBLY	18NE22B	24A-00	1
3	FRONT END ASSEMBLY	18NE22F	24A-00	1
2	SIDE WALL ASSEMBLY	18NE22S	24A-00	2
1	REAR END ASSEMBLY	18NE22E	24A-00	1

ITEM	DESCRIPTION	DWG NO.	ISSUE	QTY.
TITLE: 20'x8'x8'6" GENERAL ARRANGEMENT				
CUSTOMER:		SCALE: 1 : 30		
DESIGNED BY:		WEIGHT: KG. QTY.: 1		
CHECKED BY:		DWG No.: 18NE22G		
APPROVED BY:				
SHEET	OF	SHEETS	ISSUE:	24A-00